

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56	A1	(11) International Publication Number: WO 98/09407 (43) International Publication Date: 5 March 1998 (05.03.98)
---	----	---

(21) International Application Number: PCT/SE97/01354
(22) International Filing Date: 15 August 1997 (15.08.97)
(30) Priority Data:
9603081-2 26 August 1996 (26.08.96) SE
(71) Applicant (for all designated States except US): TELEFON-AKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).
(72) Inventor; and
(75) Inventor/Applicant (for US only): CINKLER, Tibor [HU/HU]; Bartha u. 8, H-1126 Budapest (HU).
(74) Agents: WIDEBERG, Olle et al.; Telefonaktiebolaget LM Ericsson, Patent Dept., S-126 25 Stockholm (SE).


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: METHOD FOR OPTIMISING A MOSTLY OPTICAL NETWORK

(57) Abstract

Method for forming the virtual topology (21-45) of an ATM-layer where the ATM-layer is carried over an optical network (1) where inputs such as the physical topology (2-8, 11-16) and constraints of physical nature are given, thereafter forming node-pairs with end-to-end connections according to some known optimal routing algorithm, and finally applying a non-deterministic mathematical approach to obtain an optimal virtual topology with the objective of minimising the need for necessary electrical processing (50, 60, 70, 80) in the nodes (11-16) of the network (1).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD FOR OPTIMISING A MOSTLY OPTICAL NETWORK
Technical Field of the Invention

The invention relates to a method for solving optimisation problems occurring during the design of a mostly optical ATM network.

5

Description of Related Art

The technique of finding new solutions for designing networks based on Asynchronous Transfer Mode (ATM) or on All Optical Networks (AON) is a rapidly growing area of research in telecommunication and computer business. Both ATM and AON have own methodologies for simplifying network management and switching. Whereas ATM networks apply the VP (Virtual Path) concept, i.e many connections which have a common path in a part of the network are handled (managed, switched) together, the AONs assign the wavelengths to connections in such a way that connections of the same wavelength are handled together without any electrical processing during the transmission. Optical networks employ Wavelength Division Multiplexing (WDM) and specially designed algorithms allow a high aggregate system capacity due to spatial reuse of wavelengths.

A known idea, (Mukherjee, Ramamurthy and Banerjee, "Some principles for designing a wide-area optical network" IEEE 1994, pp. 110-119), is to combine the technology of AONs with ATM technique. By using optical amplifiers and switches in a mostly optical ATM network, the number of opto-electrical conversions can be reduced significantly, which leads to better signal quality and lower delays, but from the point of view of ATM there is a problem: the VPI/VCI modification in the cell header becomes impossible. The Wavelength Division Multiplexing (WDM) technique offers a good utilization of the fibre but the

transmission capacity is divided into equal parts (channels) defined by the wavelengths used. Because of this partitioned capacity the statistical multiplexing (SM), which is another benefit of the ATM, has limits. SM can shortly be described as
5 the gain accomplished when dynamically multiplexing together channels with bursty traffic into one channel, thereby eliminating those empty timeslots which may occur in the channels due to the burstiness. The larger the capacity, the lower the effective bandwidth, therefore the resource usage is
10 more efficient.

Combining the technology of AONs with ATM technique entails a loss of performance due to the loss of SM. The total effect though, is a gain due to the enhanced performance coming from the simplified VP management.

15 A use of this combined technique implies both advantages and drawbacks. The drawbacks are that the switching must be done on three different levels (instead of two), namely: 1. Pure optical switching for VPLs; 2. VP switching (Cross connects) where the switching is done on the basis of VPIs (VPIs are changed); 3. VC
20 switching. The design procedure is computationally hard as the complexity is about the number of available wavelengths to the power of the number of nodes in the network. The main advantage though, is that many opto-electrical conversions can be avoided so that less CCs are required, thereby enhancing the
25 performance.

There is a problem in how to make the architecture of systems like this optimal, i.e. when designing backbone networks for example, one must assume full logical connectivity between the nodes in the network and try to find optimisation algorithms for
30 best using the limited number of wavelengths to accomplish a

high aggregate system capacity due to spatial reuse of wavelengths.

The architecture used in the IEEE-paper is a combination of well-known "singlehop" and "multihop" approaches as employed in many other WDM networks/proposals. The paper deals with optimising the cost, efficiency and throughput of the routing node by theoretical analysis. The optimisation is here split into two steps with the objective of minimising the average message delay caused by transfer: 1. They find and map a virtual topology into the given physical; and 2. Assign the wavelengths to links of the virtual topology. This technique brings about that the VP design is already performed in step one, meaning that the optimality criteria could be deteriorated and the delays could increase since if there are more end-to-end streams on a physical link than the allowed number of wavelengths, the paper proposes a rerouting of one of these streams. Hence, the average delay is increased as the wavelength assignment and the virtual topology forming are divided.

20 Summary

Combining ATM networks with an All Optical Network (AON) is a rather new technique with drawbacks and advantages. Here we try to design the virtual topology of an optimal ATM network on top of a AON. The optimality criterion refers here to making the ATM network "as optical" as possible, meaning that we want as long lightpaths as possible in the network without having to change the wavelength, i.e the total number of necessary wavelength changes in the network should be as few as possible, thereby minimising the need for the lightpaths to enter Crossconnects (CCs). This idea solves the problem by, and discloses a method

for, finding an optimal routing of the VPCs so that the amount of VP switching can be maximally reduced. In ATM networks is an end-to-end connection associated with a VCC (Virtual Channel Connection). One or more VCCs are established on a VP Connection (VPC) which is built of one or more VP Links (VPL) along the path of the VCC. The VPL consists of one or more VPs concatenated. Hence, the VP is a "bundle" of VCCs along one physical link.

Along a VPL the VPI/VCID is not changed. Therefore no electrical processing is needed along the VPL, which also is the objective with the invention. Since no electrical processing is needed along a VPL, the same wavelength can be assigned to all of its components, i.e VPs. In this case the VPCs using these VPLs will not have to enter in the Cross Connects (CCs). They can be switched by passive optical switches. Since the limit on the processing capacity of CCs is dependent upon the internal bus speed, applying an ATM network on top of an AON realise the use of much larger networks. The objective is to carry the cells by the virtual topology as far as possible in the optical domain. Packet forwarding from lightpath to lightpath is performed via electronic switching when required.

When we design a backbone network, full logical connectivity must be assumed, which means that every node must be able to connect every other node in the network. In general, the design consists of three problems to be solved optimally: 1. Route the VPCs; 2. Cut them into VPLs; 3. Dimension the VPLs. These problems are dependent of each other. When our model is applied, the third problem can be relaxed, instead we have a constraint: None of the VPL capacities should exceed the partition (channel) capacity. The invention proposes a two-phase method in order to

accomplish optimality as often as possible, where the first phase involves finding one (or two for reliability purposes) node-and-vertex disjoint path(s) for each node-pair and assigning them capacities according to their traffic. The objective to be minimised when routing the VPCs is the total network cost. This calls for input parameters such as position of nodes, estimated traffic demands between nodes and the costs of building physical links between them when we design the network; or estimated traffic demands between the nodes and the physical topology with capacities given when we are rerouting the VPCs. The second part of the method involves a cutting of paths between node-pairs into sequences and merging these sequences into VPLs and assigning them a wavelength. The emphasis is laid on this second part. The objective to be minimised here is the total number of cuts of a VPC or in other words, minimising the number of VPLs along a VPC. It can mathematically be expressed as a constrained discrete optimisation problem, which can be solved by stochastic optimisation (e.g Simulated Annealing or Genetic Algorithm). The novelty of the invention lies in the two step model as a whole and especially the second step with the objective of the optimisation and the constraints, i.e. the formulation of the problem and how to apply stochastic optimisation onto this problem, i.e how to match the model to the optimisation algorithm, to obtain an optimal network with a minimum of use of electric processing.

The method gives the optimal virtual topology simultaneously with the wavelength assignment! Furthermore it does not increase the transfer delays in the network because we join some of the streams if enough capacity is available instead of a rerouting of one of the streams, which is necessary in prior art as the

number of streams on a physical link are more than the number of available wavelengths.

Brief Description of the Drawing

5 Embodiments of the invention will be described in connection with a drawing on which:

- Fig. 1 shows an example of a six-node network with its physical and virtual topology, optimised according to the invention.

10 Detailed Description of Embodiments

To make the presentation of the idea and the preferred embodiment easier, an example of a network is depicted in fig 1. The drawing shows the optimal six-node 11-16 ATM network over an optical network 1 employing Wavelength Division Multiplexing, 15 WDM, or Space Division Multiplexing, Space DM. The number of nodes and the physical distance is of course arbitrary and the method shown is not limited to a network with the physical topology of that in the drawing. The nodes of fig. 1 are interconnected by seven physical links 2-8 as seen in the 20 figure. In this example we assume full logical connectivity and three different wavelengths a, b and c. With the given physical topology we obtain 15 VPCs: seven of length one (22;26;29;31;35;39;43;), six of length two (21 and 25; 24 and 44; 27 and 28; 32 and 36; 30 and 34; 37 and 40;) and two of 25 length three (23 and 45 and 41; 33 and 38 and 42). Altogether we have ten "hops", i.e. the passing of a node on the way from the originating node to the destination node, where electrical processing (wavelength reassignment and remultiplexing) could be needed if not the optimisation method according to the invention

as showed below had reduced the number of hops. The optimisation method proposed has reduced the number of hops processed by Cross Connects (CCs) in this example from 10 to 4. These points 50,60,70,80, where the streams are mixed and where we need electrical processing and buffering, are showed in figure 1.

Given the position of the nodes, the traffic matrix, the physical links and their capacities, we start with the first step of the method which involves a routing of the Originator-Destination nodepairs or VPCs on top of the physical network based on any optimality criteria without any constraints related to the optical nature of the physical layer, e.g. shortest path, least loaded path or by the multi-commodity flow routing algorithm. This step contains nothing new so it will not be explained any further except from mentioning that if not the physical links and their capacities are given initially, we can adopt any known optimality criteria to these parameters too. However, even if step one is not important standing alone, it is important in combination with the second step since it ensures that optimality is not deteriorated when applying step two. Before a thorough description of step two it is important to clear up and define the many abbreviations the ATM-technology gave birth to.

The routes are divided into basic building units, which we in this application abbreviate bbus, - each of length of one physical link, in other words, a physical link is a set of bbus. Hence, in figure 1, there are altogether 25 bbus numbered from 21 to 45. The union of all physical links 2-8 and the nodes 11-16 is the network 1. A subset of one physical link is a VP (bbu's of the same wavelength) e.g. 34, 35 and 37. Therefore a physical link is a union of VPs. VPs are disjunct sets. The VPs

cover all the bbus of a physical link. Serial grouping (union) of (one or more) VPs (of the same wavelength) is a VPL. Serial grouping of (one or more) VPLs is a VPC. An example will make this easier: The bottom right link 8 in the figure 1, contains
5 five bbus 34-38, but three VPs only. The VPC of wavelength b between node 14 and 13 which passes link 8 consists of one single VPL which consists of three VPs 33, 38 and 42, and another VP on link 8 is the VP of wavelength c, which consists of parallel bounding of three bbu's, 34, 35 and 37. The bbu 34
10 is a part of a VPC between node 12 and 16 and is a VPL built up of only one VP. Since that VPC changes wavelength there is a need for electrical processing (Cross Connecting) in node 15. The Cross Connecting is visualized by reference numeral 70. For the node-pair 15 and 16 connected by the single bbu 35, the VP
15 of wavelength c is a VPL and a VPC at the same time. The VPLs are the most important building blocks, since they are the parallel and serial grouping of bbu which do not need any processing. The VPCs only describe a sequence of VPLs used by a point-to-point stream.

20 The second step is as said based on an arbitrary first step and cuts paths between node-pairs into sequences and merges the sequences into VPLs assigning them a wavelength. The problem rapidly grows with the number of nodes and the number of available wavelengths. Already in the example given in figure 1
25 with six nodes and three available wavelengths and 25 bbu the state space consists of 3^{25} different states. Hence, the problem is extremely complex for such a small example. According to the idea, the problem will be significantly reduced if the state space is tightened by starting with assigning one and the
30 same wavelength to all logical links of length one between adjacent nodes. In figure 1 this is illustrated by bbu

22;26;29;31;35;39;43 which all have been assigned wavelength c. This assignment does not deteriorate the generality of the model even though it simplifies it. The total complexity will be 3^7 times lower: 3^{18} . The problem now starts to take form. To
5 continue with step two in the model, a mathematical formulation of the problem to be solved by the method is needed. In this first way described below a non-deterministic global optimisation, like e.g Simulated Annealing with "Cooling Schedule" or Genetic Algorithm or Tabu Search, is used to obtain
10 the Objective Function which is to minimise the total number of VPLs (minimise the number of hops for each VPC). Below is shown according to the invention how the problem can be formulated to be solved by Simulated Annealing

The Inputs are: The physical topology; One or more optimally
15 chosen paths; The number of wavelengths supported by each fiber; Estimated busy-hour traffic demand of each node-pair; The transmission capacity of the fiber for each wavelength. The algorithm will give following Outputs: VPs, i.e the parallel bundling of bbus; VPLs, i.e the serial bundling of VPs along a
20 VPC and the wavelength assigned to every single VPL. There are a number of constraints which must not be violated: The number of wavelengths/links may not exceed the given value; Transmission capacity of each wavelength should not be exceeded; Maximal number of hops along a VPC can be limited. The algorithm
25 searches its way to global optima by making "elementary movements" which in this case is to change the wavelength of an arbitrary bbu in the network. There can be multiple global optima. An elementary movement is here defined as changing the wavelength of an arbitrary bbu and check whether the VPs in
30 adjacent links can be concatenated to a VPL or not. If they are of the same wavelength and if all bbus of that wavelength are

crossing both links then we concatenate these VPs into a VPL. After we evaluate the Objective Function: we count the total number of VPLs and if the constraints are violated we add a penalty term. While trying to minimise the Objective Function, the states where penalty is added are accepted with lower and lower probabilities. This is because of the "cooling" in Simulated Annealing. In Simulated Annealing we are randomly doing elementary movements. If the Objective Function has better value than in the previous step, it is accepted with higher probability, if worse with lower probability. Accepting a state means that we will move in the next step of the algorithm to one of the neighbours (adjacent states in the multidimensional state-space) of that state. While doing cooling, all states are in the beginning accepted with almost the same probability; at the end the probability of acceptance is getting almost deterministic: better movement is accepted, worse is refused.

When applying Simulated Annealing (with cooling schedule,) tests have shown that we get result in about 10^4 steps. This result is a global optimum with probability about 0,8. If we repeat the whole procedure 10 times the probability of finding global optimum will be $1 - (10^{-7})$.

In another embodiment of the invention's step one and two, the optimisation procedure would work just as well if we instead of having multiple wavelengths, had multiple fibres (i.e Space Division Multiplexing instead of WDM). This would imply a use of cables containing more fibres and a use of the same wavelength in the whole network. In the example depicted in figure 1 this would mean that each physical link 2-8, would contain three fibres. The whole example would be exactly equivalent as the abovedescribed, with the difference that the three wavelengths

a, b and c instead would denote three different fibres, each using the same wavelength. A VP would then be defined as one fibre in a physical link. Between fibres of different physical links, optical switching can easily be performed. One natural
5 cause is then that if we form a VPL from multiple VPs (fibres), no traffic stream can enter or exit at nodes between these VPs.

Claims

1. Method for forming the virtual topology of an ATM-layer where the ATM-layer is carried over an optical Wavelength Division Multiplexing (WDM) network (1) as the physical layer, initially
5 at least given: the position of the nodes (11-16); the traffic matrix; and the number of wavelengths (a,b,c) supported by each physical link (2-8), c h a r a c t e r i z e d in that firstly, the end-to-end traffic streams are routed on top of the physical network by any known method in an optimal way, e.g Shortest
10 Path, Least Loaded Path or Multicommodity Flow Model, and that secondly, grouping the basic building units (bbus) (21-45) serially and parallelly by applying a non-deterministic algorithm, e.g Simulated Annealing, with the objective function of minimizing the total number of VPLs, given constraints
15 limiting the performance, as inputs.

2. Method according to claim 1, c h a r a c t e r i z e d in that the grouping of the basic building units (bbus) (21-45) is done by changing the wavelength (a,b or c) of an arbitrary bbu;
20 checking whether the VPs in adjacent links can be concatenated to a VPL or not; concatenate said VPs into a VPL if said VPs are of the same said wavelength (a,b or c) and if all bbus of said wavelength belong to traffic streams which crosses all these VPs of said VPL; evaluating the objective function by counting the
25 number of VPLs; add a penalty term to the Objective Function in that state if at least one of the constraints are violated and then accepting said state with decreasing probability.

3 Method according to claim 2, c h a r a c t e r i z e d in that
30 the steps of claim 2 are repeated a predefined number of times or until no more improvement according to the objective function

is reached, choosing the obtained state-space as the virtual topology for the network.

4. Method according to any of claims 1-3, c h a r a c t e r -
i z e d in that the state-space is tightened by assigning all
basic building units (bbus), which carry the traffic of adjacent
nodepairs (22;26;29;31;35;39;43), the same wavelength before
applying the non-deterministic algorithm.

5. Method for forming the virtual topology of an ATM-layer where
the ATM-layer is carried over an optical Space Division
Multiplexing network (1) as the physical layer, initially at
least given: the position of nodes (11-16); the traffic matrix;
and the number of different fibres (a,b,c) in each physical
link, wherein each fibre employ the same wavelength, c h a r -
a c t e r i z e d in that firstly, the end-to-end traffic
streams are routed on top of the physical network by any known
method in an optimal way, e.g Shortest Path, Least Loaded Path
or Multicommodity Flow Model, and that secondly, grouping the
basic building units (bbus) (21-45) serially and parallelly by
applying a non-deterministic algorithm, e.g Simulated
Annealing, with the objective function of minimizing the total
number of necessary changes of fibres, given constraints
limiting the performance, as inputs.

6. Method according to claim 5, c h a r a c t e r i z e d in
that the grouping of the basic building units (bbus) (21-45) is
done by changing the fibre (a,b or c) reserved for an arbitrary
bbu; checking whether the VPs in adjacent links can be
concatenated to a VPL or not; concatenate said VPs into a VPL if

all bbus of said fibre (VP) belong to traffic streams which crosses all the fibres (VPs) of said VPL; evaluating the objective function by counting the number of VPLs; add a penalty term to the Objective Function in that state if at least one of
5 the constraints are violated; accepting said state with decreasing probability.

7. Method according to claim 6, c h a r a c t e r i z e d in that the steps of claim 6 are repeated a predefined number of times or until no more improvement according to the Objective
10 Function is reached, choosing the obtained state-space as the virtual topology for the network.

8. Method according to any of claim 5-7, c h a r a c t e r - i z e d in that the state-space is tightened by assigning all basic building units (bbus) which carry the traffic of adjacent
15 nodes a reserved fibre (22;26;29;31;35;39;43) before applying the non-deterministic algorithm.

1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01354

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4736363 A (RAYMOND AUBIN ET AL), 5 April 1988 (05.04.88), abstract -----	1-8

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

12 December 1997

Date of mailing of the international search report

16-12-1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

MIKAEL SOLLERHED
Telephone No. +46 8 782 25 00

International application No.
PCT/SE 97/01354

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4736363 A	05/04/88	CA 1245327 A	22/11/88
<hr/>			

1/1




Fig. 1

THIS PAGE BLANK (USPTO)